

| MANUFACTURER MODEL | John Deere X304 (4WS) (2008) |
|--|--|
| Engine | |
| Power | 17 hp (12.7 kW)* |
| *Engine hp is provided by engine mfr. for comparison purposes. Actual operating hp will be less. | |
| Displacement | 28.8 cu. in. (472 cc) |
| Manufacturer | Kawasaki |
| Cylinders | V-twin, cast-iron liners |
| Type | OHV, oil filter |
| Charging System | 15 amp regulated |
| Battery | 195 cold-crank amps |
| Choke/Speed Control | Separate levers |
| Fuel Tank Capacity | 3.5 U.S. gallon |
| Transmission | |
| Type | K46 automatic |
| Control | Twin Touch pedals |
| Cruise Control | Standard |
| Forward Speed | 0-5.5 mph |
| Reverse Speed | 0-4.0 mph |
| Chassis | |
| Frame | Welded heavy-duty |
| Primer/Paint | E-coat/powder |
| Front Tires | 15x6-6 |
| Rear Tires | 20x10-10 |
| Front Axle | Cast iron |
| Hood Material | Xenoy |
| Hourmeter | Yes |
| Service Interval Decal | Yes |
| Tool Tray | Yes |
| Cupholder | Yes |
| Steering | |
| Type | 4-wheel steer |
| Turning Radius | 15 in. |
| Uncut Circle Radius | 16 in. (42X mower) |
| Spindle Bushings | Metal, replaceable |
| Seat | |
| Seat Back Height | 15 in. open back |
| Fore-aft Adjustment | 7 in. while seated |
| Seat Suspension | Three-position |
| Lift System | |
| Type | Foot pedal with optional adjustable spring assist |
| Mower Cut Height | 1-4 in., 13 position |
| Cut Height Increments | 0.25 in. |
| Preset Cut Height | Yes |
| Mower | |
| Type | Side discharge |
| Mower Cutting Width | 42 in. |
| Mower Deck Material | .105 in. (42X) |
| Mower Wheel Adjustment | 4-position, tool required |
| Mower Drive System | In-line belt, electric PTO |
| Mower Attachability | |
| Front Draft Arms | Two-point mounting |
| Rear Draft Arms | 2 pins and spring clips |
| Belt Tension | Spring |
| Mower Wheels Rotate | No |
| Safety | |
| Meets ANSI Standard | Yes |
| OPEI Label | Yes |
| Backup Protection | RIO |
| Safety Video | Yes |
| Buyer's Notes | |
| Note 1 | 4-wheel steering for unmatched maneuverability and trimming capability |
| Note 2 | Xenoy hood reduces sound, won't rust |
| Note 3 | One-piece hood for easy service access |
| U.S. Warranty | 4 year/300 hour |

Optional Attachments

| | |
|--------------------|--|
| Mowers | 42X (standard) |
| Rear Bagger | 7 bu. 2-bag |
| Powered Collection | No |
| Mulching System | Yes |
| Front Thatcher | 38, 46, 54 in. |
| Front Blade | 44 in. |
| Front Bumper | Standard, also styled bumper and brush guard options |
| Brush Guard | Yes |
| Bucket Holder | Yes, double |
| Tow-Behind Tools | 15 |

Contact Coufal-Prater Equipment, LTD, at tome@cpebry.com for more detailed information.

Prices are subject to change without notice. In all cases, current published price lists and incentive program bulletins will take precedence.