

MANUFACTURER	John Deere
MODEL	X320 (2008)
Engine	
Power	22 hp (16.4 kW)*
*Engine hp is provided by engine mfr. for comparison purposes. Actual operating hp will be less.	---
Displacement	41.2 cu. in. (675 cc)
Manufacturer	Kawasaki
Cylinders	V-twin, cast-iron liners
Type	OHV, oil filter
Charging System	15 amp regulated
Battery	195 cold-crank amps
Choke/Speed Control	Separate levers
Fuel Tank Capacity	3.5 U.S. gallon
Transmission	
Type	K58 automatic
Control	Twin Touch pedals
Cruise Control	Standard
Forward Speed	0-5.8 mph
Reverse Speed	0-3.5 mph
Chassis	
Frame	Welded heavy-duty
Primer/Paint	E-coat/powder
Front Tires	15x6.5-8
Rear Tires	22x11-10
Front Axle	Cast iron
Hood Material	Xenoy
Hourmeter	Yes
Service Interval Decal	Yes
Tool Tray	Yes
Cupholder	Yes
Steering	
Type	2-wheel steer
Turning Radius	16 in.
Uncut Circle Radius	21 in. (48X mower)
Spindle Bushings	Metal, replaceable
Seat	
Seat Back Height	15 in. open back
Fore-aft Adjustment	7 in. while seated
Seat Suspension	Three-position
Lift System	
Type	Foot pedal with adjustable spring assist
Mower Cut Height	1-4 in., 13 position
Cut Height Increments	0.25 in.
Preset Cut Height	Yes
Mower	
Type	Side discharge
Mower Cutting Width	48 in.
Mower Deck Material	.120 in. (48X)
Mower Wheel Adjustment	7-position, pin and spring clip
Mower Drive System	In-line belt, electric PTO
Mower Attachability	
Front Draft Arms	Two-point mounting
Rear Draft Arms	No-tools spring-loaded J-pins
Belt Tension	Spring with release lever
Mower Wheels Rotate	Yes, 90 degrees for easy mower removal
Safety	
Meets ANSI Standard	Yes
OPEI Label	Yes
Backup Protection	RIO
Safety Video	Yes
Buyer's Notes	
Note 1	Xenoy hood material won't dent or rust
Note 2	One-piece hood for easy service access
Note 3	Durable E-coat primer and powder paint finish
U.S. Warranty	4 year/300 hour

Optional Attachments

Mowers	48X (standard)
Rear Bagger	No
Powered Collection	7 bu. Power Flow
Mulching System	Yes
Front Thatcher	38, 46, 54 in.
Front Blade	44 in.
Front Bumper	Standard, also styled bumper and brush guard options
Brush Guard	Yes
Bucket Holder	Yes, single and double
Tow-Behind Tools	15

Contact Coufal-Prater Equipment, LTD, at tome@cpebry.com for more detailed information.

Prices are subject to change without notice. In all cases, current published price lists and incentive program bulletins will take precedence.