

<b>MANUFACTURER</b>	<b>John Deere</b>
<b>MODEL</b>	<b>X340 (2008)</b>
<b>Engine</b>	
Power	25 hp (18.6 kW)*
*Engine hp is provided by engine mfr. for comparison purposes. Actual operating hp will be less.	---
Displacement	41.2 cu. in. (675 cc)
Manufacturer	Kawasaki
Cylinders	V-twin, cast-iron liners
Type	OHV, oil filter
Charging System	15 amp regulated
Battery	195 cold-crank amps
Choke/Speed Control	Separate levers
Fuel Tank Capacity	3.5 U.S. gallon
<b>Transmission</b>	
Type	K58 automatic
Control	Twin Touch pedals
Cruise Control	Standard
Forward Speed	0-5.8 mph
Reverse Speed	0-3.5 mph
<b>Chassis</b>	
Frame	Welded heavy-duty
Primer/Paint	E-coat/powder
Front Tires	15x6.5-8
Rear Tires	22x11-10
Front Axle	Cast iron
Hood Material	Xenoy
Hourmeter	Yes
Service Interval Decal	Yes
Tool Tray	Yes
Cupholder	Yes
<b>Steering</b>	
Type	2-wheel steer
Turning Radius	16 in.
Uncut Circle Radius	18 in. (54X mower)
Spindle Bushings	Metal, replaceable
<b>Seat</b>	
Seat Back Height	15 in. open back
Fore-aft Adjustment	7 in. while seated
Seat Suspension	Three-position
<b>Lift System</b>	
Type	Foot pedal with adjustable spring assist
Mower Cut Height	1-4 in., 13 position
Cut Height Increments	0.25 in.
Preset Cut Height	Yes
<b>Mower</b>	
Type	Side discharge
Mower Cutting Width	54 in.
Mower Deck Material	.135 in. (54X)
Mower Wheel Adjustment	7-position, pin and spring clip
Mower Drive System	In-line belt, electric PTO
<b>Mower Attachability</b>	
Front Draft Arms	Two-point mounting
Rear Draft Arms	No-tools spring-loaded J-pins
Belt Tension	Spring with release lever
Mower Wheels Rotate	Yes, 90 degrees for easy mower removal
<b>Safety</b>	
Meets ANSI Standard	Yes
OPEI Label	Yes
Backup Protection	RIO
Safety Video	Yes
<b>Buyer's Notes</b>	
Note 1	Xenoy hood material will not dent or rust
Note 2	One-piece hood for easy service access
Note 3	Durable E-coat primer and powder paint finish
U.S. Warranty	4 year/300 hour

**Optional Attachments**

Mowers	54X (standard)
Rear Bagger	No
Powered Collection	7 bu. Power Flow
Mulching System	Yes
Front Thatcher	38, 46, 54 in.
Front Blade	44 in.
Front Bumper	Standard, also styled bumper and brush guard options
Brush Guard	Yes
Bucket Holder	Yes, single and double
Tow-Behind Tools	15

Contact Coufal-Prater Equipment, LTD, at [tome@cpebry.com](mailto:tome@cpebry.com) for more detailed information.

Prices are subject to change without notice. In all cases, current published price lists and incentive program bulletins will take precedence.