



JOHN DEERE 458 STANDARD ROUND BALER

Specifications (click here)

To compare with other manufacturers models hold down the [Control](#) key on your keyboard and click on the following link:

<http://www.deere.com/specsapp/CustomerCompetitorDetailsServlet?sbu=Ag&userAction=GETCOMPONELLS&pciModel=0458CE&displayModelName=458%20Twine%20Baler&tM=FR&pNbr=0458CE>

Safety

- Gate lockout
- Built-in transport lights

Driveline

- Constant-velocity PTO
- PTO driveline holder

Pickup

- Regular pickup offers large feed opening and low-profile, mid-mounted pickup

Forming chamber

- Vertical forming chamber
- Round bars on starter roll
- Staggered belt rolls with extra service life belt splices
- Mechanical bale-shape indicators allow operator to make square-shoulder, dense bales easily

Twine-wrapping system

- Double-twine hydraulic arm system
- Double electric twine arm system
- Twine-cutting knife and anvil

Density-control system

- Hydraulic bale tensioning provides uniform bale density throughout the bale

Monitor system

- Mechanical bale-shape indicators allow operator to make square-shoulder, dense bales easily

Product features are based on published information at the time of publication. Product features are subject to change without notice. Contact tome@cpebry.com for more information.