



JOHN DEERE 468 SILAGE SPECIAL ROUND BALER

Specifications (click here)

To compare with other manufacturers models hold down the [Control](#) key on your keyboard and click on the following link:

<http://www.deere.com/specsapp/CustomerCompetitorDetailsServlet?sbu=Ag&userAction=GETCOMPONELLS&pciModel=0468SE&displayModelName=468%20SilageSpecial&tM=FR&pNbr=0468SE>

Safety

- Gate lockout
- Built-in transport lights

Driveline

- Constant-velocity PTO
- PTO driveline holder

Pickup

- MegaWide™ Plus pickup with MegaTough™ pickup teeth offers super capacity

Forming chamber

- Vertical forming chamber
- Round bars on starter roll
- Exclusive DiamondTough™ belts with plate-type splices
- BaleTrak™ Pro monitor-controller

Twine and net

- Automatic electric twine-wrapping system
- Twine-cutting knife and anvil
- Twine storage
- Exclusive COVER-EDGE™ surface wrap option

Density-control system

- Hydraulic bale tensioning provides uniform bale density throughout the bale
- Variable core kit

Monitor system

- BaleTrak™ Pro monitor-controller
- Automatic electric twine-wrapping system

Bale ejection system

- Bale push bar

Product features are based on published information at the time of publication. Product features are subject to change without notice. Contact tome@cpebry.com for more information.